

serie/series:

EASY-C



Compressori alta professionalita' - bistadio
trasmissione a cinghia - lubrificati



Oil-lubricated high-performance - double-stage compressors with belt drive



Compresseurs à haute performance - deux stades entraînement par courroie - lubrifiés



Hochprofessionelle zweistufig verdichter Riemenantrieb mit schmieresystem



Compressores alta profesionalidad - de dos etapas transmisión de correa - lubricados

EC 270/5,5 T



CARATTERISTICHE TECNICHE - TECHNICAL DATA

COD.	TYPE	Liters	Cil.	lt/min.	CFM	m³/h	bar	psi	Hp/Cv	kW	Volt/ph	r.p.m.	Kg	Lbs	A x B x h	Euro
TRIFASI CARRELLATI - THREE PHASES/PORTABLE																
91053	EC 150/5,5T*	150 C	2	585	20,6	36	11	159	5,5	4	400/3	1,400	129	283	132x50x103	1.420,00
91054	EC 200/5,5T	200 C	2	585	20,6	36	11	159	5,5	4	400/3	1,400	139	306	145x50x107	1.575,00
91055	EC 270/5,5T	270 C	2	585	20,6	36	11	159	5,5	4	400/3	1,400	155	341	155x57x118	1.650,00
91056	EC 500/5,5T	500 C	2	585	20,6	36	11	159	5,5	4	400/3	1,400	215	473	203x67x131	2.135,00
91057	EC 200/7,5T	200 C	2	798	28,2	49	11	159	7,5	5,5	400/3	1,400	139	306	145x50x107	1.790,00
91058	EC 270/7,5T	270 C	2	798	28,2	49	11	159	7,5	5,5	400/3	1,400	155	341	155x57x118	1.900,00
91059	EC 500/7,5T	500 C	2	798	28,2	49	11	159	7,5	5,5	400/3	1,400	215	473	203x67x131	2.405,00
TRIFASI FISSI - THREE PHASES/STATIONARY																
91060	EC 200/5,5TF	200 F	2	585	20,6	36	11	159	5,5	4	400/3	1,400	139	306	145x50x107	1.490,00
91061	EC 270/5,5TF	270 F	2	585	20,6	36	11	159	5,5	4	400/3	1,400	155	341	155x57x118	1.635,00
91062	EC 500/5,5TF	500 F	2	585	20,6	36	11	159	5,5	4	400/3	1,400	215	473	203x67x131	2.085,00
91063	EC 200/7,5TF	200 F	2	798	28,2	49	11	159	7,5	5,5	400/3	1,400	139	306	145x50x107	1.745,00
91064	EC 270/7,5TF	270 F	2	798	28,2	49	11	159	7,5	5,5	400/3	1,400	155	341	155x57x118	1.860,00
91065	EC 500/7,5TF	500 F	2	798	28,2	49	11	159	7,5	5,5	400/3	1,400	215	473	203x67x131	2.345,00
91066	EC 270/7,5TFΔ	270 F	2	798	28,2	49	11	159	7,5	5,5	400/3	1,400	155	341	155x57x118	2.625,00
91067	EC 500/7,5TFΔ	500 F	2	798	28,2	49	11	159	7,5	5,5	400/3	1,400	215	473	203x67x131	2.995,00

EC 500/10 TF



CARATTERISTICHE TECNICHE - TECHNICAL DATA

COD.	TYPE	Liters	Cil.	lt/min.	CFM	m³/h	bar	psi	Hp/Cv	kW	Volt/ph	r.p.m.	Kg	Lbs	A x B x h	Euro
TRIFASI FISSI - THREE PHASES/STATIONARY																
91068	EC 270/10TF	270 F	4V	1.084	38,3	67	11	159	10	7,5	400/3	1,150	206	453	155x64x118	2.520,00
91069	EC 500/10TF	500 F	4V	1.084	38,3	67	11	159	10	7,5	400/3	1,150	266	585	203x67x131	3.015,00
91070	EC 270/10TFΔ	270 F	4V	1.084	38,3	67	11	159	10	7,5	400/3	1,150	215	473	155x64x118	3.385,00
91071	EC 500/10TFΔ	500 F	4V	1.084	38,3	67	11	159	10	7,5	400/3	1,150	274	603	203x67x131	3.860,00
91072	EC 500/15TFΔ	500 F	4V	1.310	46,2	81	11	159	15	11	400/3	1,150	281	618	203x67x131	4.495,00
91073	EC 900/15TFΔ	900 F	4V	1.310	46,2	81	11	159	15	11	400/3	1,150	386	849	212x85x161	5.450,00

* consegna 40 giorni

Δ = Avviamento stella/triangolo • Delta-star starting • Demarrage etoile/triangle • Stern-/Dreieckanlasser • Arranque estrella/triangulo